



R

LIMITES ADMISSIBLES :

Pression : 1 MPa

Vitesse : 15 m/s

Température: -30 °C ~ 200 °C



| Modèle | d1 | d3 | d7 | L1 | L3 |
|--------|----|----|------|------|------|
| P10R | 10 | 20 | 18.1 | 20.5 | 5.5 |
| P12R | 12 | 22 | 20.6 | 23.5 | 5.5 |
| P13R | 13 | 25 | 23.1 | 28 | 6 |
| P14R | 14 | 25 | 23.1 | 28 | 6 |
| P15R | 15 | 29 | 26.9 | 30 | 7 |
| P16R | 16 | 29 | 26.9 | 30 | 7 |
| P17R | 17 | 29 | 26.9 | 30 | 7 |
| P18R | 18 | 33 | 30.9 | 32 | 8 |
| P19R | 19 | 33 | 30.9 | 33 | 8 |
| P20R | 20 | 33 | 30.9 | 33 | 8 |
| P21R | 21 | 38 | 35.4 | 33 | 8 |
| P22R | 22 | 38 | 35.4 | 33 | 8 |
| P24R | 24 | 38 | 35.4 | 35 | 8 |
| P25R | 25 | 40 | 38.2 | 35.5 | 8.5 |
| P28R | 28 | 46 | 43.3 | 39 | 9 |
| P30R | 30 | 46 | 43.3 | 39 | 9 |
| P32R | 32 | 46 | 43.3 | 39 | 9 |
| P35R | 35 | 50 | 53.5 | 50.5 | 11.5 |
| P38R | 38 | 58 | 60.5 | 50.5 | 11.5 |
| P40R | 40 | 58 | 60.5 | 50.5 | 11.5 |

- Bague fixe (Ceramic/SiC/TC)
- Bague tournante (Carbon/ SiC/TC)
- Joint secondaire (NBR/ EPDM/VITON)
- Ressort & autres (S.S/SUS304/SUS316)

