



ID

LIMITES ADMISSIBLES :

Pression : 0.3 MPa

Vitesse : 10 m/s

Temperature : -30 °C ~ 200 °C



| Modèle | d1 | d3 | d7 | L1 | L2 | L3 |
|--------|----|----|----|----|----|----|
| P13 ID | 13 | 25 | 25 | 36 | 5 | 5 |
| P14 ID | 14 | 30 | 30 | 36 | 5 | 5 |
| P15 ID | 15 | 30 | 30 | 36 | 5 | 5 |
| P16 ID | 16 | 30 | 30 | 36 | 5 | 5 |
| P20 ID | 20 | 38 | 44 | 49 | 7 | 7 |
| P25 ID | 25 | 44 | 50 | 51 | 7 | 7 |
| P30 ID | 30 | 50 | 57 | 59 | 9 | 8 |
| P35 ID | 35 | 58 | 64 | 61 | 9 | 9 |
| P40 ID | 40 | 64 | 70 | 64 | 11 | 9 |
| P45 ID | 45 | 66 | 70 | 65 | 10 | 9 |
| P50 ID | 50 | 72 | 80 | 69 | 10 | 9 |

- Bague fixe (Ceramic/SIC/TC)
- Bague tournante (Carbon/ SIC/TC)
- Joint secondaire (NBR/ EPDM/VITON)
- Ressort & autres (S.S/SUS304/SUS316)

