



N

OPERATING LIMITS

Pressure: 0.6 MPa

Speed: 10 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d3	d6	d7	L1	L3
P6N	6	18	8	22	14	4
P8N	8	18	10	22	15	4
P10N	10	24	12	26	21	8
P12N	12	24	14	25	21	8
P13N	13	24	15	26	19.5	5.5/8
P14N	14	28	16	28.5	21	8
P14N SP	14	32	16	29.5	21	8
P15N	15	28	16	28.5	21	8
P15N SP	15	38	16	39	21	8
P16N	16	28	18	29.5	21	8
P16NM	16	32	18	29.5	21	8
P16NSP	16	39	18	38	21	8
P17N	17	39	19	42	21	8
P18N	18	39	20	42	21	8
P19N	19	39	21	42	21	8
P20N	20	39	22	42	21	8
P20N SP	20	42	24	45	23	10
P22N	22	42	24	45	23	10
P24N	24	47	26	50	23.5	10
P24N SP	24	47	26	50	23.5	10
P25N	25	42	27	50	23.5	10
P28N	28	54	31	57	25	10
P30N	30	54	33	57	25	10
P32N	32	54	35	57	25	10
P35N	35	60	38	63	26	10
P38N	38	65	41	68	30	12
P40N	40	65	43	68	30	12
P45N	45	70	48	73	32	12
P50N	50	85	52	88	38	15
P55N	55	85	58	88	38	15
P60N	60	105	63	110	45	15
P65N	65	105	64	110	45	15

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/ SiC/TC)
- Secondary Seal (NBR/ EPDM/VITON)
- Spring & Other Parts (S.S/SUS304/SUS316)

