



**OPERATING LIMITS**

Pressure: 1 MPa

Speed: 12 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d3	d6	d7	L1	L3
P14I	14	26.5	23	28	25	7
P15	15	26.5	23	28	25	7
P16I	16	26.5	23	32	26	8
P17I	17	30	26	32	32	10
P18I	18	32.5	25	35	26	10
P19I	19	32.5	25	35	26	10
P20I	20	35.5	27	38	28	10
P22I	22	37.5	29	40	28	10
P24I	24	40	32	39	40	10
P25I	25	42.0	32	44	29	10
P28I	28	45.5	34	46	30	10
P30I	30	48.0	38	50	31	10
P32I	32	50.0	40	54	33	10
P35I	35	54.5	44	58	36	10
P38I	38	58.5	46	60	37	10
P40I	40	62.5	48	64	38	10
P45I	45	66.5	52	66	40	10
P50I	50	72.5	58	72	42	10
P55I	55	72	60	75	44	12
P60I	60	80	65	80	52	12
P65I	65	85	70	85	52	13

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/ SiC/TC)
- Secondary Seal (NBR/ EPDM/VITON)
- Spring & Other Parts (S.S/SUS304/SUS316)

