



IMS

OPERATING LIMITS

Pressure: 1.2MPa

Speed: 10 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d2	d3	d7	L1	L3
P14 IMS	14	26.5	28.5	24.6	23.5	6.5
P15 IMS	15	26.5	28.5	24.6	24.5	7.5
P16 IMS	16	26.5	28.5	28	25.5	8.5
P18 IMS	18	29	32	30	28.5	9
P19 IMS	19	33	37	35	21.5	8.5
P20 IMS	20	33	37	35	30	8.5
P22 IMS	22	33	37	35	30	8.5
P24 IMS	24	38	42.5	38	31	8.5
P25 IMS	25	38	42.5	38	31.5	8.5
P28 IMS	28	44	49	42	36.5	10
P30 IMS	30	44	49	45	38	11.5
P32 IMS	32	46	53.5	48	39	11.5
P35 IMS	35	50	57	52	40.5	12
P38 IMS	38	53	59	55	41.3	11.3
P40 IMS	40	55	62	58	41.8	11.8
P42 IMS	42	58	65.5	62	43.2	13.2
P45 IMS	45	60	68	64	42.8	12.8
P50 IMS	50	65	74	69.3	43.3	12.8
P53 IMS	53	70	78.5	72.3	46.5	13.5
P55 IMS	55	72	81	75.4	49.5	14.5
P60 IMS	60	79	88.5	80.4	52.5	14.5
P65 IMS	65	84	93.5	85.4	54.2	14.2

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/ SiC/TC)
- Secondary Seal (NBR/ EPDM/VITON)
- Spring & Other Parts (S.S./SUS304/SUS316)

