



# IM2

## OPERATING LIMITS

Pressure: 1.2MPa

Speed: 10 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d2	d3	d7	L1	L3
P14 IM2	14.0	26.5	28.5	25.0	35.0	6.6
P16 IM2	16.0	26.5	28.5	27.0	35.0	6.6
P18 IM2	18.0	29.0	32.0	33.0	37.5	7.5
P20 IM2	20.0	33.0	37.0	35.0	37.5	7.5
P22 IM2	22.0	33.0	37.0	37.0	37.5	7.5
P24 IM2	24.0	38.0	42.5	39.0	40.0	7.5
P25 IM2	25.0	38.0	42.5	40.0	40.0	7.5
P28 IM2	28.0	44.0	49.0	43.0	42.5	7.5
P30 IM2	30.0	44.0	49.0	45.0	42.5	7.5
P32 IM2	32.0	46.0	53.5	48.0	42.5	7.5
P35 IM2	35.0	50.0	57.0	50.0	42.5	7.5
P38 IM2	38.0	53.0	59.0	56.0	45.0	9.0
P40 IM2	40.0	55.0	62.0	58.0	45.0	9.0
P45 IM2	45.0	60.0	68.0	63.0	45.0	9.0
P48 IM2	48.0	63.0	70.5	66.0	45.0	9.0
P50 IM2	50.0	65.0	74.0	70.0	47.5	9.5
P55 IM2	55.0	72.0	81.0	75.0	47.5	11.0
P60 IM2	60.0	79.0	88.5	80.0	52.5	11.0
P65 IM2	65.0	84.0	93.5	85.0	52.5	11.0

- **Stationary Ring** (Ceramic/SiC/TC)
- **Rotary Ring** (Carbon/ SiC/TC)
- **Secondary Seal** (NBR/ EPDM/VITON)
- **Spring & Other Parts** (S.S/SUS304/SUS316)

