



# IM2S

## OPERATING LIMITS

Pressure: 1.2MPa

Speed: 10 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d2	d3	d7	L1	L3
P14 IM2S	14.0	26.5	28.5	25.0	35.0	6.6
P15 IM2S	15.0	28	28	27.5	35.5	6.5
P16 IM2S	16.0	26.5	28.5	27.0	35.0	6.6
P17 IM2S	17.0	29.5	31.2	33.5	35.0	7.5
P18 IM2S	18.0	29.0	32.0	33.0	37.5	7.5
P19 IM2S	19.0	35.5	35.5	35.5	37.5	7.5
P20 IM2S	20.0	33.0	37.0	35.0	37.5	7.5
P22 IM2S	22.0	33.0	37.0	37.0	37.5	7.5
P24 IM2S	24.0	38.0	42.5	39.0	40.0	7.5
P25 IM2S	25.0	38.0	42.5	40.0	40.0	7.5
P28 IM2S	28.0	44.0	49.0	43.0	42.5	7.5
P30 IM2S	30.0	44.0	49.0	45.0	42.5	7.5
P32 IM2S	32.0	46.0	53.5	48.0	42.5	7.5
P35 IM2S	35.0	50.0	57.0	50.0	42.5	7.5
P38 IM2S	38.0	53.0	59.0	56.0	45.0	9.0
P40 IM2S	40.0	55.0	62.0	58.0	45.0	9.0
P45 IM2S	45.0	60.0	68.0	63.0	45.0	9.0
P50 IM2S	50.0	65.0	74.0	70.0	47.5	9.5
P55 IM2S	55.0	72.0	81.0	75.0	47.5	11.0
P60 IM2S	60.0	79.0	88.5	80.0	52.5	11.0
P65 IM2S	65.0	84.0	93.5	85.0	52.5	11.0

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/ SiC/TC)
- Secondary Seal (NBR/ EPDM/VITON)
- Spring & Other Parts (S.S./SUS304/SUS316)

